Tork Heavy-Duty Cleaning Cloth

Colour: White **Format:** Folded

benefit

- exelCLEAN™ for higher cleaning effiency
- Multipurpose - handles most cleaning tasks
- Good oil and water absorption
- Strong enough for though scrubbing
- Food contact approved

1

product properties

article	system	Ply	Print	Colour
530171	W7 - Handy box system, W7 - Handy box system	1	no	White

description

This strong and absorbent multipurpose cloth works with most solvents. It is designed to protect your hands from heat and metal scraps. The cloth provides a professional cleaning result thanks to the exelCLEAN™ effect.

Tork Heavy-Duty Cleaning Cloth

Colour: White **Format:** Folded

shipping data

consumer unit

EAN	7322540057560
pieces	200
height	238 mm
width	236 mm
length	395 mm
volume	22.2 dm3
net weight	2637 g
gross weight	2935 g

transport unit

EAN	7322540057577
pieces	200
consumer units	1
material	Carton
height	238 mm
width	236 mm
length	395 mm
volume	22.2 dm3
net weight	2.64 kg
gross weight	2.94 kg

pallet

EAN	7322540275902
pieces	12000
consumer units	60
height	1353 mm
width	1000 mm
length	1200 mm
volume	1.3 m3
net weight	158.22 kg
gross weight	176.10 kg

Tork Heavy-Duty Cleaning Cloth

Colour: White **Format:** Folded

environmental

Content

Cellulose pulp

Polypropylene fibres

Polyester fibres

Chemicals

Material

Cellulose pulp

Cellulose pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals to remove the lignin between the fibres. The pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities.

There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free).

ECF is based on oxygene, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone.

ECF is used in this product.

Polypropylene

Polypropylene fibres is produced from polypropylene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.

Polyester

Polyester fibre is produced from terephtalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.

Chemicals

Both functional and process chemicals are used. The functional chemical used

is a wetstrength agent. The wetstrength agent is a polyamide (from polyamidine/epichlorhydrinepolymer) with a very high affinity to the fibre.

The process chemical used is a surfactant.

Production

This product is produced at Suameer mill, The Netherlands, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

Food Contact

This product fulfils the legislative requirements for Food Contact materials, confirmed by external certification performed by ISEGA. The product is safe for wiping food contact surfaces and may also come occasionally into

contact with foodstuffs for a short period of time.

Disposing / destruction of used product

This product is mainly used for industrial processes and might through use be contaminated with different substances. This will determine how the used product will be handled / disposed of / destructed. The product itself is suitable for incineration. Contact local authorities before destruction.