



Tork Industrial Cleaning Cloth

Colour: Grey



benefit

- exelCLEAN™ for higher cleaning efficiency
- Good oil and water absorption
- Soft and flexible
- Works well with most solvents
- Food contact approved



product properties

article	system	Roll Length	Roll Diameter	Number of Sheets	Ply	Print	Colour
520304	W1 - Wipers wall/floor/standard system, W1 - Wipers wall/floor/standard system	361 m	38 cm	950	1	no	Grey

description

A soft and flexible cloth that is excellent in tight spaces, and ideal for cleaning oil and grease. The cloth provides a professional cleaning result thanks to the exelCLEAN™ effect.



Tork Industrial Cleaning Cloth

Colour: Grey

shipping data

consumer unit

EAN	7322540057461
pieces	1
height	437 mm
width	391 mm
length	391 mm
volume	66.8 dm ³
net weight	10090 g
gross weight	11095 g

transport unit

EAN	7322540057478
pieces	1
consumer units	1
material	Carton
height	437 mm
width	391 mm
length	391 mm
volume	66.8 dm ³
net weight	10.09 kg
gross weight	11.10 kg

pallet

EAN	7322540275773
pieces	12
consumer units	12
height	1037 mm
width	1000 mm
length	1200 mm
volume	0.8 m ³
net weight	121.08 kg
gross weight	133.14 kg



environmental

Content

Cellulose pulp

Polypropylene fibres

Polyester fibres

Chemicals

Material

Cellulose pulp

Cellulose pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals to remove the lignin between the fibres. The pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities.

There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free).

ECF is based on oxygene, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone.

ECF is used in this product.

Polypropylene

Polypropylene fibres is produced from polypropylene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.

The fibres used contains black pigments.

Polyester

Polyester fibre is produced from terephtalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.

Chemicals

Both functional and process chemicals are used. The functional chemical used

is a wetstrength agent. The wetstrength agent is a polyamide (from polyamidine/epichlorhydrinepolymer) with a very high affinity to the fibre.

The process chemical used is a surfactant.

Production

This product is produced at Suameer mill, The Netherlands, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

Food Contact

This product fulfils the legislative requirements for Food Contact materials, confirmed by external certification



Tork Industrial Cleaning Cloth

Colour: Grey

performed by ISEGA. The product is safe for wiping food contact surfaces and may also come occasionally into contact with foodstuffs for a short period of time.

Disposing / destruction of used product

This product is mainly used for industrial processes and might through use be contaminated with different substances. This will determine how the used product will be handled / disposed of / destructed. The product itself is suitable for incineration. Contact local authorities before destruction.